

Truck-mounted concrete pump

Output up to 160 m³/h Delivery pressure up to 130 bar



Putzmeister




Note: Standard version. Dimensions and weights depend on truck and pump model. Dimensions in mm, MB-Actros 3241 as example

Technical Data

Boom M 42-5								
Reach height	m	41.6						
Horizontal gross reach net	m m	37.6 34.7						
Reach depth max.	m	29.5						
Unfolding height	m	8.6						
End hose length	m	4						
Number of arms	5							
Folding system	Roll-Z-folding (RZ)							
Delivery line	DN 125/5.5							

Pump	BSF		.14 H	.16 H	.16 H LS	
Rod side	Output	m³/h	140	160	-	
	Delivery pressure	bar	70	85	-	
	Strokes	1/min.	27	31	-	
Piston side	Output	m³/h	88	108	160	
	Delivery pressure	bar	112	130	85	
	Strokes	1/min.	17 21		26	
	Delivery cylinder	ø mm	230	230	250	
	Stroke	mm	2100	2100	2100	

Delivery line boom max. 85 bar. All data maximum theoretical.



Delivery scope

	Standard	Options Package *	Options Package Plus		Standard	Options Package *	Options Package Plus
support plates 4x in magazine	•			traffic permission kit		•	•
spotlights 4x for illumination support area	٠			radio remote control prop.incl. CPC with output remote control by regulator, engine start/stop			
concrete hopper RS 900 with agitator RS 900 M at BSF .16 H LS	•					•	•
diagnose interface,				splash guard foldable on rubber collar		•	•
central for electric and hydraulic	•			lighting in toolbox		•	•
remote control CPC with 25m cable				EOC (Ergonic output control)		•	•
with output remote control by regulator, engine start/stop	•			central lubrication hopper, electrical		•	•
central lubrication strip hopper	٠			horn at the boom		•	•
rubber collar	٠			working search light on boom for hopper illumination			•
painting: arm assembly RAL 3020 signalred	•			flashlights for 4 support legs front and rear			•
painting: pump MB 1227 chrome yellow	٠						-
flushing water pump 160 l/min 25 bar	•			high pressure water pump 100 bar with dry-run protection			•
water tank	٠			vibrator, electrical			•
concrete line DN125, 5,5" 133x4	•			hard metal wear parts kit			•
concrete line DN125, 5,5" PM 22 twin layer		•		* ෦෫෬	ommen	ided in	Europe
concrete line DN125, 5,5" PM 252 Proline			•				•
support plates 4x + timber wood 8x1000 in magazine		•	•	special: Ergon Please see quotation for e			
OSS one side support		•	•			Sirvery	scope.

Putzmeister AG · Postfach 2152 · D-72629 Aichtal · Telefon (0 71 27) 599-0 · Telefax (0 71 27) 599-520 · Telex 7266113